



HHP



BL4 21-200

Standard equipment:

- Gun with rotating coupling.
- Lance with nozzle-holder.
- Power cable 5 m
- High pressure hose 10 m

- Integrated elastic joint
- Auxiliary motor for burner air cooling and mechanical two ways fuel pump.

- Control panel with protection cover
- Water leak detection, low fuel cut-off and stand-by complete shutdown.

- High pressure detergent dosing pump.
- 4 poles double roller bearing water cooled motor.

Optional:

- Flame sensor kit
- Remote control kit
- Low temperature internal insulation protection/heating

Versions available on request:

- With mechanic coin operating system
- With header tank and anti scale device
- With complete stainless steel structure:

HHPX 1211 LP RA cod. 8.624.0609
 HHPX 1515 LP RA cod. 8.624.0610
 HHPX 2015 LP RA cod. 8.624.0611
 HHPX 2021 LP RA cod. 8.624.0612

	HHPV 1211 LP RA	HHPV 1515 LP RA	HHPV 2015 LP RA	HHPV 2021 LP RA
Code	8.624.0601	8.624.0602	8.624.0603	8.624.0604
operat. pressure/max	30÷120 bar	30÷150 bar	30÷200 bar	30÷200 bar
operat. pressure/max	435÷1740 psi	435÷2175 psi	435÷2900 psi	435÷2900 psi
delivery rate	330÷660 l/h	450÷900 l/h	450÷900 l/h	630÷1260 l/h
delivery rate	1.45÷2.91 GPM	1.98÷3.96 GPM	1.98÷3.96 GPM	2.77÷5.55 GPM
abs. power/voltage	3000W-230V-50Hz	5000W-400V-50Hz	7300W-400V-50Hz	9700W-400V-50Hz
RPM	1450	1450	1450	1450
diesel tank/detergent tank	20/20 l.-5.28/5.28 gal	20/20 l.-5.28/5.28 gal	20/20 l.-5.28/5.28 gal	20/20 l.-5.28/5.28 gal
max temp. inlet/outlet	40 °C / 140 °C	40 °C / 140 °C	40 °C / 140 °C	40 °C / 140 °C
fuel consumption/heat output	4,72 l/h-58kW	4,72 l/h-58kW	4,72 l/h-58kW	6,6 l/h-88kW
machine dimensions	87,5 x 55 x h 184 cm	87,5 x 55 x h 184 cm	87,5 x 55 x h 184 cm	87,5 x 55 x h 184 cm
machine weight	178 Kg	178 Kg	178 Kg	178 Kg